

Shrink Frame Type „Profi2“

Without open flame



Palett size	800 x 1200 mm
	and 1000 x 1200 mm
Palett height	2000 mm
Foil width	80 –200 μ
Palett capacity	40 – 80 Paletts / hour
(depends on pallet size)	
Gas pressure at least 25 mbars	
All drives controlled by frequency inverters	

Special options on request

Options:

- Palett lift device for palett under shrink
- Palett conveyor
- Security fence according to CE

Operation mode

The palett will be centered under the ring burner. Then the shrink cycle begins. The shrink frame is moving down, over the palett. After starting the shrink cycle, the shrink frame is moving up with adjustable speed. All sides of the paletts will be shrinked even. On the top edge of the palett, the shrink frame is staying for a short time, to keep the „top shrink“. After that, the shrink frame is moving to the origin position. Now the palett can be extracted.

Without open flame

The shrinking technology is according to the latest knowledges concerning performance, security and optimized using of power.

The „PROFI“ can also be integrated later into a full-automatically plant with conveyors and foil bag pulling system. Therefore, we can offer: Roll and chain conveyors, and all varieties of conveyor technology

Technical data (standard) :

H-8600 Siófok Sarok u. 6.
www.pack-modern.com

Fax+36 84 314041 Mobil +36 309 707 477
E-mail:info@pack-modern.com